

Product Description

Blown Rapeseed Oil
CAS no 95193-59-2

Blown rapeseed oils offer formulators excellent lubricity, high VI, high flash point, relatively good low temperature properties, biodegradability and from sustainable resources. In the dry TOST test, performance is similar to TMP tri oleates, though from a higher initial acidity value.

Sales Specifications

Properties	Units	Specifications	Typical values	Test Method
Appearance	-	Clear viscous liquid	Clear viscous Liquid	Visual
Colour	Gardner	max 13	10	ASTM D1544
Specific gravity 20°C	g/ml	0.970 - 0.980	-	ASTM D4052
Viscosity 40°C	cSt	650 - 750	740	ASTM D445
Viscosity 100°C	cSt	-	60	ASTM D445
Viscosity Index	-	-	148	ASTM D445
Viscosity 20°C	dPa.s	-	28	ASTM D4287
Acid Value	mgKOH/g	Max 15	12	ASTM D974

Liabilities. All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply. Please see our website for details.

Boedal Ltd, 11 Portland Street, Southampton SO14 7EB, England
Company number : 6578081 VAT number : GB 936 634 892
www.boedal.com e-mail : info@boedal.com

Tel + 44 (0)2380 089083 Fax + 44 (0)2380 335784

Boedal is ISO9001 Certified