

BOEDAL Ltd

Refined Rapeseed oil

Product Description

Refined Rapeseed Oil
CAS no 8002-13-9

Refined rapeseed oil finds widespread use in metalworking oils, concrete mould oils, steel casting lubricants etc.

Sales Specifications

Properties	Units	Specifications	Typical values	Test Method
Appearance	-	Clear yellow liquid	Clear yellow liquid	Visual
Colour	Lovibond 51/4"	$\leq 1.5R$	-	AOCD Cc 13e-92
Density 20°C	g/ml	0.914 - 0.917	-	ASTM D4052
Viscosity 40°C	cSt	-	36	ISO 6883
Viscosity 100°C	cSt	-	8	ASTM D445
Viscosity Index	-	-	204	ASTM D445
Flash point COC	°C	-	>220	ASTM D92
Pour point	°C	-	-21	ASTM D97
Acid Value	mgKOH/g	≤ 0.2	-	ISO 6618
Refractive index	n40D	-	1.465 - 1.467	
Saponification value	mgKOH/g	-	182 - 193	
Iodine value	gI2/100g	-	105 - 126	

Liabilities. All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply. Please see our website for details.

Boedal Ltd, 11 Portland Street, Southampton SO14 7EB, England
Company number : 6578081 VAT number : GB 936 634 892
www.boedal.com e-mail : info@boedal.com

Tel + 44 (0)2380 089083 Fax + 44 (0)2380 335784