## **BOEDAL Ltd**

## **Boester SSO 94**

## **Product Description**

Stand oil mixture soyabean / linseed oil CAS no 68122-64-5

Boester SSo 94 is a stand oil made from a 80/20 mixture of soybean and linseed oils. The polymers are made under anaerobic conditions and at high temperature. Stand oils are thought to cross link via the double bonds of the triglceride.

Sales Specifications				
Properties	Units	<b>Specifications</b>	Typical values	<b>Test Method</b>
Appearance	-	Clear viscous liquid	Clear viscous Liquid	Visual
Colour	Gardner	max 10	-	ASTM D1544
Viscosity 40°C	cSt	-	2449	ASTM D445
Viscosity 100°C	cSt	-	196	ASTM D445
Viscosity Index	-	-	203	ASTM D445
Viscosity 20°C	dPa.s	85 - 95	90	<b>ASTM D4287</b>
Pour point	°C	-	3	ASTM D97
Flash point	°C	-	256	ASTM D92
lodine value	gl2/100g	75 - 95	-	

Liabilities. All recommendatons for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply. Please see our website for details.

Boedal Ltd, 11 Portland Street, Southampton SO14 7EB, England Company number: 6578081 VAT number: GB 936 634 892 www.boedal.com e-mail: info@boedal.com

Tel + 44 (0)2380 089083 Fax + 44 (0)2380 335784

Boedal is ISO9001 Certified

Version 1.0